

INTERNAL RELEASE AGENTS AD LUBRICANTS RECOMMENDATIONS FOR USE

POLYMER	PRODUCT										
	PAT [®] RU 55/P	PAT [®] 44/04	PAT [®] 44/05	PAT [®] 757/C	PAT [®] 760	PAT [®] 760/DL	PAT [®] 764/A	PAT [®] 777	PAT [®] 799/F	PAT [®] 799/FS	PAT [®] 2790
ACM		✓	✓		✓	✓		✓			✓
AU/EU											✓
BR	✓										
CR		✓	✓		✓	✓			✓	✓	
CSM					✓	✓					
ECO		✓	✓		✓	✓		✓			✓
EPDM	✓	✓	✓		✓	✓		✓			✓
EVA		✓	✓		✓	✓	✓				
FPM		✓	✓					✓			✓
HNBR		✓	✓					✓			
IIR		✓	✓	✓			✓				
NBR	✓	✓	✓		✓	✓					✓
NR	✓	✓	✓		✓	✓					✓
SBR					✓	✓					✓
SIR		✓	✓								✓
TR					✓	✓					

ACM = ACRYLESTER-RUBBER

AU/EU = URETHANE-RUBBER

BR = BUTADIENE-RUBBER

CR = CHLORBUTADIENE-RUBBER

CSM = CHLORSULFONATED POLYETHYLENE

ECO = EPICHLORHYDRINE-COPOLYMERS

EPDM = ETHYLENE-PROPYLENE-TERPOLYMERS

EVA = ETHYLENE-VINYLACETATE-COPOLYMERS

FPM = FLUOROCARBON-RUBBER

IIR = BUTYL-RUBBER

NBR = NITRILE-RUBBER

NR = NATURAL-RUBBER

SBR = STYRENE-BUTADIENE-RUBBER

SIR = SILICONE-RUBBER

TR = THERMOPLASTIC RUBBERS

Products for the use with rubber types not shown here are available upon request.

All information is based upon laboratory test and industrial experience, and is intended for use, at their own risk by persons having a technical skill. We assume no liability in connection with the use of the product described herein.